



# HP Latex 365 Printer

Produce a wide range of outdoor and indoor applications with this full-feature 64-inch printer



## Expand your applications—beat client expectations

- Print on traditional signage substrates and beyond—up to 64 inches—print textiles with the ink collector.<sup>1</sup>
- Reach more indoor spaces, like healthcare—water-based HP Latex Ink prints are odorless.<sup>1</sup>
- Enjoy efficient, automated double-sided banner printing.
- Produce sharp, consistent, repeatable image quality with high-efficiency curing, 6 colors, and 1200 dpi.

## Same day delivery—for highly demanding turnarounds

- High quality at high speeds—334 ft<sup>2</sup>(31 m<sup>2</sup>)/hr high-speed outdoor quality with HP OMAS, HP Latex Optimizer.<sup>3</sup>
- Reach production speeds and avoid wait time—prints come out completely dry and ready to finish and deliver.
- Gain productivity—reduce time between jobs with continuous printing.
- You can minimize damage risk—scratch resistance is comparable to hard-solvent inks on SAV and PVC banner.<sup>2</sup>

## Keep your running costs low—boost your capacity

- Increase production time and reduce time monitoring the printer—automatic, reliable, low-maintenance printing.
- Save time—HP Custom Substrate Profiling and i1 embedded spectrophotometer make ICC profiling automatic.<sup>4</sup>
- Maintain high image quality over the life of the printer with user-replaceable HP Thermal Inkjet printheads.
- Monitor your printer remotely with the free HP Latex Mobile app.<sup>5</sup>

For more information, please visit <http://www.hp.com/go/latex365>

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at <https://kcc.hp.com/>

<sup>1</sup> Performance may vary depending on media—for more information, see <http://www.hp.com/go/mediasolutionslocator>. For best results, use textiles that do not stretch. The ink collector is required for porous textiles. Odorless prints: there is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

<sup>2</sup> Estimates by HP Image Permanence Lab on a range of media. Scratch-resistance comparison based on testing HP Latex Inks and representative hard-solvent inks. Outdoor display permanence tested according to SAE J2527 using HP Latex Inks on a range of media, including HP media; in a vertical display orientation in simulated nominal outdoor display conditions for select high and low climates, including exposure to direct sunlight and water; performance may vary as environmental conditions change. Laminated display permanence using HP Clear Gloss Cast Overlaminate. Results may vary based on specific media performance.

<sup>3</sup> Banner-quality prints in outdoor (4-pass 4-color) mode.

<sup>4</sup> ICC profiling with the spectrophotometer does not support uncoated textiles and backliits.

<sup>5</sup> HP Latex Mobile is compatible with Android™ 4.1.2 or later and iOS 7 or later, and requires the printer and the smart phone or tablet to be connected to the Internet.

# Technical specifications

## Print

Printing modes	91 m <sup>2</sup> /hr - Max Speed (1 pass) 31 m <sup>2</sup> /hr - Outdoor High Speed (4 pass) 23 m <sup>2</sup> /hr - Outdoor Plus (6 pass) 17 m <sup>2</sup> /hr - Indoor Quality (8 pass) 14 m <sup>2</sup> /hr - Indoor High Quality (10 pass) 6 m <sup>2</sup> /hr - Backlits, Textiles, and Canvas (16 pass) 5 m <sup>2</sup> /hr - High Saturation Textiles (20 pass)
----------------	--

Print resolution	Up to 1200 x 1200 dpi
------------------	-----------------------

Ink types	Water-based HP Latex inks
-----------	---------------------------

Ink cartridges	7 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer)
----------------	---

Cartridge size	775 ml
----------------	--------

Printheads	6 (2 cyan/black, 2 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer)
------------	--

Long-term print-to-print repeatability	Average ≤ 1 dE2000, 95% of colors ≤ 2 dE2000 <sup>1</sup>
--	---

## Media

Handling	Roll feed, take-up reel, automatic cutter (for vinyl, paper-based media, backlit polyester film)
----------	--

Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, fabrics, mesh, textiles <sup>2</sup>
-------------	---

Roll size	254 to 1625-mm rolls (580 to 1625-mm rolls with full support)
-----------	---

Maximum roll weight	42 kg
---------------------	-------

Maximum roll diameter	250 mm
-----------------------	--------

Thickness	Up to 0.5 mm
-----------	--------------

Applications	Banners; Displays; Double-sided banners; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Traffic signage
--------------	--

## Connectivity

Interfaces	Gigabit Ethernet (1000Base-T)
------------	-------------------------------

## Dimensions (W x D x H)

Printer	2561 x 840 x 1380 mm
---------	----------------------

Shipping	2795 x 760 x 1250 mm
----------	----------------------

Operating area	2761 x 1840 mm
----------------	----------------

## Weight

Printer	216 kg
---------	--------

Shipping	303.5 kg
----------	----------

What's in the box	HP Latex 365 Printer, printheads, maintenance cartridge, ink collector, output platen protector, printer stand, spindle, take-up reel, variable front tension kit, loading accessory, user maintenance kit, edge holders, quick reference guide, setup poster, documentation software, power cords
-------------------	--

## Environmental ranges

Operating temperature	15 to 30°C
-----------------------	------------

Operating humidity	20 to 80% RH (non-condensing)
--------------------	-------------------------------

## Acoustics

Sound pressure	55 dB(A) (operating), 39 dB(A) (idle), <15 dB(A) (sleep)
----------------	--

Sound power	7.4 B(A) (operating), 5.7 B(A) (idle), <3.5 B(A) (sleep)
-------------	--

## Power

Consumption	3.9-4.6 kW (4.6 kW peak) (printing), 85 W (ready), <2.5 W <sup>3</sup> (sleep) (<8 W <sup>4</sup> with DFE), <0.15 W (off)
-------------	--

Requirements	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 16 A max per power cord
--------------	--

## Certification

Safety	IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM)
--------	---

Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI)
-----------------	---

Environmental	ENERGY STAR; WEEE; RoHS (EU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT Bronze; OSHA; CE marking compliant
---------------	---

Warranty	1 Year Limited Warranty (Next Business Day On-Site)
----------	---

# Ordering information

## Product

V8L39A	HP Latex 365 Printer
--------	----------------------

## Accessories

F0M56A	HP Series 300 64-in Printer 2-in Spindle
F0M58A	HP Series 300 64-in Printer 3-in Spindle
F0M59A	HP Latex User Maintenance Kit
F0M64A	HP Series 300/500 Edge Holder Kit
T7U74A	HP Series 300/500 Ink Collector Foam Kit

## Original HP printing supplies

CZ677A	HP 831 Cyan/Black Latex Printhead
CZ678A	HP 831 Yellow/Magenta Latex Printhead
CZ679A	HP 831 Light Magenta/Light Cyan Latex Printhead
CZ680A	HP 831 Latex Optimizer Printhead
CZ681A	HP 831 Latex Maintenance Cartridge
CZ688A	HP 831B 775-ml Black Latex Ink Cartridge
CZ689A	HP 831B 775-ml Cyan Latex Ink Cartridge
CZ690A	HP 831B 775-ml Magenta Latex Ink Cartridge
CZ691A	HP 831B 775-ml Yellow Latex Ink Cartridge
CZ692A	HP 831B 775-ml Light Cyan Latex Ink Cartridge
CZ693A	HP 831B 775-ml Light Magenta Latex Ink Cartridge
CZ706A	HP 831 775-ml Latex Optimizer Ink Cartridge

## Original HP large format printing materials

HP Permanent Gloss Adhesive Vinyl (REACH certified <sup>5</sup> )
HP Backlit Polyester Film
HP PVC-free Durable Smooth Wall Paper (REACH <sup>5</sup> , FSC <sup>6</sup> , UL GREENGUARD GOLD certified <sup>7</sup> )
HP Premium Poster Paper (FSC <sup>6</sup> certified <sup>6</sup> )

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

## Service and Support

U9JE3E	HP 2 year NBD with Defective Media Retention
U9JE4E	HP 3 year NBD with Defective Media Retention
U9JE7PE	HP 1 year Post Warranty NBD with Defective Media Retention
U9JE8PE	HP 2 year Post Warranty NBD with Defective Media Retention

<sup>1</sup> Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.

<sup>2</sup> Performance may vary depending on media—for more information, see <http://www.hp.com/go/mediasolutionslocator>. For best results, use textiles that do not stretch. The optional ink collector is required for porous textiles.

<sup>3</sup> Excluding Type 2 DFE (Digital Front End) as defined in Energy Star<sup>®</sup> Product Specification for Imaging Equipment version 3.1.

<sup>4</sup> Total power measured in sleep mode including the Digital Front End contained on the product.

<sup>5</sup> This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.

<sup>6</sup> BMG trademark license code FSC-C115319, see <http://www.fsc.org>. HP trademark license code FSC-C017543, see <http://www.fsc.org>. Not all FSC-certified products are available in all regions.

<sup>7</sup> UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <http://www.ul.com/gg> or <http://www.greenguard.org>

